

Revision Date: 09/14/2017

Version:36

Americas Styrenics LLC encourages and expects you to read and understand the entire SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

### SECTION 1 : Product And Company Identification

#### 1.1. **Product Identifier**

**Product Name** STYRON™ 484 Natural Polystyrene

Product Form Pellets or Granules

#### 1.2. **Relevant Use**

Recommended Use A polystyrene plastic - For industrial conversion as a raw material for

manufacture of articles or goods. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or

technical service representative.

#### 1.3. **Supplier Information**

Americas Styrenics LLC Suite 1200 24 Waterway Avenue The Woodlands, TX 77380 USA

Telephone: 844-512-1212

Email: productsteward@amsty.com

#### 1.4. **Emergency Telephone**

**Chemtrec®** 800-424-9300 **Local Emergency Contact** 800-510-8510

#### SECTION 2 : Hazard Identification

#### 2.1. **GHS Classification**

#### **GHS Classification**

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### 2.2. **GHS Label Elements**

#### **GHS-US Labelling**

No labelling required

#### **Other Hazards** 2.3.

Solid or dust may cause irritation or corneal injury due to mechanical Eye Contact

Styron™ is a trademark of Trinseo LLC.

09/27/2021 1/11

Safety Data Sheet

action. Elevated temperatures may generate vapor levels sufficient to cause eye irritation. Effects may include discomfort and redness.

Skin Contact : Under normal processing conditions, material is heated to elevated

temperatures; contact with the material may cause thermal burns.

Inhalation : Dust may cause irritation to upper respiratory tract (nose and throat).

Vapors/fumes released during thermal processing may cause

respiratory irritation.

Ingestion : May cause choking if swallowed.

### 2.4. Additional Physical Information

If converted to small particles during further processing, handling, or by other means, may form combustible dust concentration in air.

### SECTION 3 : Composition / Information On Ingredients

#### 3.1. Substance

Not Applicable

#### 3.2. Mixture

Name	CAS - No.	%	GHS Classification
Styrene, 1,3-butadiene copolymer	9003-55-8	>= 94	No labelling required
White mineral oil (petroleum)	8042-47-5	<= 5	No labelling required

#### Section 4 : First Aid Measures

### 4.1. Description of Preventative and First Aid Measures

Eye Contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice/attention.

Skin Contact : If molten material comes in contact with the skin, do not apply ice but

cool under ice water or running stream of water. DO NOT attempt to remove the material from skin. Removal could result in severe tissue

damage.

Inhalation : IF INHALED: Remove Person to fresh air and keep at rest in a position

comfortable for breathing.

Ingestion : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

#### 4.2. Important Symptoms and Effects

Eye Contact : No Additional Information.

Skin Contact : No Additional Information.

Inhalation : No Additional Information.

09/27/2021 2/11

Safety Data Sheet

Ingestion : May cause gastrointestinal blockage

#### 4.3. Immediate Medical Attention and Special Treatment

Notes to Physician: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

### Section 5: Fire-Fighting Measures

#### 5.1. Extinguishing Media

Extinguishing Media : In case of fire: Use water spray for extinction. Use dry chemical powder

for extinction. Use carbon dioxide for extinction. Use foam for extinction.

Unsuitable Extinguishing Media : No Additional Information.

#### 5.2. Specific Hazards

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon dioxide. Carbon monoxide.

#### 5.3. Advice for Firefighters

Special Fire Fighting Procedures : No Additional Information.

Protective Equipment for

Firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and

protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or

not used, fight fire from a protected location or safe distance.

Unusual Fire & Explosion

Hazards

Pneumatic conveying and other mechanical handling operations can

generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate. Dense smoke is produced when

product burns.

#### Section 6: Accidental Release Measures

#### 6.1. Personal Precautions and Emergency Procedures

General Measures : Spilled material may cause a slipping Hazard

#### 6.1.1 For Non-Emergency Personnel

Emergency Procedures : No Additional Information.

#### 6.1.2 For Emergency Responders

Protective Equipment : Use personal protective equipment as required. Refer to Section 8,

Exposure Controls.

Emergency Procedures : Prevent from entering into soil, ditches, sewers, waterways and/or

groundwater.

#### 6.2. Environmental Precautions

09/27/2021 3/11

Safety Data Sheet

No Additional Information.

### 6.3. Methods for Clean Up

Spill Cleanup Methods : Sweep up. Recover spilled material if possible. Collect in suitable and

properly labeled containers. Refer to Section 13, Disposal

Considerations.

#### 6.4. Reference to Other Sections

Refer to Section 8, Exposure Controls. Refer to Section 13, Disposal Considerations.

### Section 7 : Handling and Storage

### 7.1. Precautions for Safe Handling

Precautions for Safe Handling : Pneumatic conveying and other mechanical handling operations can

generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate. Dense smoke is produced when product burns. Avoid breathing dust/fume/vapors.\'20 Workers should be protected from the possibility of contact with molten resin. Do not get molten material in eyes, on skin or clothing. Dust can be ignited by static displayers. No experience the product of the product of the product of the postions.

discharge Keep away from heat/sparks/open flames. No smoking.

Hygiene Measures : Refer to Section 8, Exposure Controls.

#### 7.2. Conditions for Safe Storage

Technical Measures : Ground/bond container and receiving equipment. Take precautionary

measures against static discharge.

Storage Conditions : Store in a well-ventilated place. Store in a dry place. Store in

accordance with good manufacturing practices (GMP).

Incompatible Materials : No data available for this product.

Storage Area : Keep container tightly closed in a cool, well-ventilated place.

Special Packaging Rules : Store with proper labeling.

### Section 8: Exposure Controls

#### 8.1. Control Parameters

None Established

#### 8.2. Exposure Controls

Appropriate Engineering Controls : No Additional Information.

Personal Protective Equipment

(PPE)

Protective Glasses, Protective Clothing, Gloves

09/27/2021 4/11

Safety Data Sheet







Hand Protection : Consistent with general hygienic practice for any material, skin contact

should be minimized. Use gloves with insulation for thermal protection, when needed. Use gloves to protect from mechanical injury. Selection of

gloves will depend on the task.

Eye Protection : Wear safety glasses with side shields. If there is potential for exposure

to particles which could cause eye discomfort, wear chemical goggles. If

exposure causes eye discomfort, use a full-face respirator.

Skin Protection : No precautions other than clean body-covering clothing should be

needed.

Respiratory Protection : Respiratory protection should be worn when there is a potential to

exceed the exposure limit requirements or guidelines.

**Environmental Exposure** 

Controls

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust

ventilation may be necessary for some operations.

Other Information : Wash hands before smoking or eating

#### Section 9 : Physical and Chemical Properties

#### 9.1. Physical and Chemical Properties

Physical State : Solid.

Color : Natural

Odor : Odorless to mild

Odor Threshold : No test data available

pH : Not applicable

Freezing Point : Not applicable

Melting Point : No test data available

Boiling Point (760 mmHg) and

**Boiling Range** 

Not applicable

Flash Point : Not applicable

Evaporation Rate : Not applicable to solids

Flammability (solid, gas) : Not applicable

Flammability Limit - Upper (%) : Not applicable

09/27/2021 5/11

Safety Data Sheet

Flammability Limit - Lower (%) : Not applicable

Vapor Pressure : Not applicable

Relative Vapor Density (air=1) : Not applicable

Relative Density (H2O=1) : 1.04 - 1.06 Estimated.

Solubility in Water : Negligible

Partition coefficient: n-

octanol/water

: No data available for this product.

Autoignition Temperature : No test data available

Decomposition Temperature : No data available.

Viscosity : Not applicable

Molecular Weight : No test data available

Henry's Law Constant (H) :

### Section 10 : Stability and Reactivity

#### 10.1. Reactivity

None known.

#### 10.2. Stability

Stable under recommended storage conditions. See Storage, Section 7.

#### 10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur

#### 10.4. Conditions to Avoid

Store at temperatures not exceeding 300°C/572°F. Exposure to elevated temperatures can cause product to decompose

#### 10.5. Incompatible Materials

None known.

### 10.6. Hazardous Decomposition Products

Decomposition products depend upon temperature, air supply and the presence of other materials. Processing may release fumes and other decomposition products. At temperatures exceeding melt temperatures, polymer fragments can be released. Fumes can be irritating. Decomposition products can include and are not limited to: Combustible gases.

### Section 11 : Toxicological Information

#### 11.1. Information on Toxicological Effects

09/27/2021 6/11

Safety Data Sheet

#### **Acute Toxicity**

Ingestion : Single dose oral LD50 has not been determined.

Skin : Typical for this family of materials. Estimated LD50, Rabbit > 2,000

mg/kg

Inhalation : The LC50 has not been determined.

#### Serious Eye Damage/Eye Irritation

Solid or dust may cause irritation or corneal injury due to mechanical action. Elevated temperatures may generate vapor levels sufficient to cause eye irritation. Effects may include discomfort and redness.

#### Skin Corrosion/Irritation

Under normal processing conditions, material is heated to elevated temperatures; contact with the material may cause thermal burns.

#### **Repeated Dose Toxicity**

Not Classified.

### **Chronic Toxicity**

#### **Germ Cell Mutagenicity:**

Genotoxicity in Vitro : Not Classified.

Genotoxicity in Vivo : Not Classified.

#### Carcinogenicity

Not Classified.

#### **Developmental Toxicity**

Not Classified.

#### **Reproductive Toxicity**

Not Classified.

#### **Target Organ Toxicity**

Specific Target Organ Toxicity

(Single Exposure)

Not Classified

Specific Target Organ Toxicity

(Repeated Exposure)

Not Classified.

Aspiration Hazard : Not Classified.

Potential Adverse Human Health

**Effects** 

No Additional Information.

Symptoms/Injuries After

Inhalation

No Additional Information.

09/27/2021 7/11

Safety Data Sheet

Symptoms/Injuries After Skin

Contact

No Additional Information.

Symptoms/Injuries After Eye

Contact

: No Additional Information.

Symptoms/Injuries After

Ingestion

No Additional Information.

### Section 12 : Ecological Information

#### 12.1. Toxicity

#### **Data for Component:** Styrene, 1,3-butadiene copolymer (9003-55-8)

Not expected to be acutely toxic to aquatic organisms. Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

#### Data for Component: White mineral oil (petroleum) (8042-47-5)

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

#### Fish Acute & Prolonged Toxicity

LC50, Lepomis macrochirus (Bluegill sunfish), static test, 96 h, > 10,000 mg/l

LL50, Oncorhynchus mykiss (rainbow trout), static test, 96 h, > 100 mg/l

LL50, Leuciscus idus (Golden orfe), static test, 96 h, > 10,000 mg/l

#### **Aquatic Invertebrate Acute Toxicity**

LL50, Daphnia magna (Water flea), static test, , , > 100 mg/l

#### 12.2. Persistence and Degradability

#### Data for Component: Styrene, 1,3-butadiene copolymer(9003-55-8)

Based on information for a similar material:

#### Data for Component: White mineral oil (petroleum)(8042-47-5)

Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

#### **OECD Biodegradation Tests:**

Biodegradation	Exposure Time	Method	10 Day Window
0 - 24 %	28 d	OECD 301B Test	fail

#### **Indirect Photodegradation with OH Radicals:**

Rate Constant	Atmospheric Half-life	Method
8.28E-12 cm3/s	1.291 d	Estimated.

#### Theoretical Oxygen Demand: 3.50 mg/g

#### 12.3. Bioaccumulative Potential

#### Data for Component: White mineral oil (petroleum)(8042-47-5)

Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Bioconcentration Factor (BCF): 1,900; Fish; Estimated.

#### 12.4. Mobility

09/27/2021 8/11

Safety Data Sheet

No Additional Information.

#### 12.5. Other Adverse Effects

No Additional Information.

### Section 13 : Disposal Considerations

Sewage Disposal : Do not empty into drains. Do not dump into sewers, on the ground, or

Recommendation into any body of water.

Waste Disposal : Dispose of contents/container to an appropriate treatment and disposal

Recommendation facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Additional Information : FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred

options include sending to a licensed, permitted: Recycler. Reclaimer.

Incinerator or other thermal destruction device.

Ecology - waste materials : No Additional Information.

#### Section 14: Transportation Information

#### 14.1. UN Number

CFR : Not Regulated

ADR : Not Regulated

TDG : Not Regulated

IMDG : Not Regulated

IATA : Not Regulated

#### 14.2. Proper Shipping Name

CFR : Not Regulated

ADR : Not Regulated

TDG : Not Regulated

IMDG : Not Regulated

IATA : Not Regulated

### 14.3. Additional Information

CFR : Not Available

ADR : Not Available

TDG : Not Available

IMDG : Not Available

09/27/2021 9/11

Safety Data Sheet

IATA : Not Available

### Section 15 : Regulatory Information

#### 15.1. US Federal Regulations

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard : No Delayed (Chronic) Health Hazard : No Fire Hazard : No Reactive Hazard : No Sudden Release of Pressure : No

Hazard

#### 15.2. International Regulations

#### **Notification Status**

Toxic Substances Control Act : All components of this product are on the TSCA Inventory or are exempt

(TSCA) from TSCA Inventory requirements under 40 CFR 720.30

CEPA - Domestic Substances : All substances contained in this product are listed on the Canadian

List (DSL) Domestic Substances List (DSL) or are not required to be listed.

#### **Ozone Depleting Potential:**

This substance is not in Annex I of Regulation (EC) No 1005/2009 on substances that deplete the ozone layer.

#### 15.3. US State Regulations

#### California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

Component	CAS#	Amount
Ethylbenzene	100-41-4	<= 175 PPM
Styrene	100-42-5	<= 450 PPM

In March 2008, the Office of Environmental Health Hazard Assessment's (OEHHA) Proposition 65 Department proposed an NSRL of 54 µg/day (inhalation) for ethylbenzene.

In April 2016, the Office of Environmental Health Hazard Assessment's (OEHHA) Proposition 65 Department proposed an NSRL of 27 µg/day for styrene.

The objective of the warning statement above is to comply with the Prop 65 statute.

For guidance on Prop 65 labeling requirements for your products, please refer to the workbook published by the Plastics Foodservices Packaging Group available by calling the Customer Information number found on page 1 of this SDS.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

Component	CAS#	Amount
White mineral oil (petroleum)	8042-47-5	<= 5 %

09/27/2021 10/11

Safety Data Sheet

# Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

#### Section 16 : Other Information

Product Literature : Additional information on this product may be obtained by calling your

sales or customer service contact.

Recommended Uses and

Restrictions

Not Available

Revision : 09/14/2017

6.3

Most recent revision(s) are noted by the bold, double bars in left-hand

margin throughout this document.

Legend

N/A : Not Available W/W : Weight/Weight

OEL : Occupational Exposure Limit
STEL : Short Term Exposure Limit
TWA : Time Weighted Average

ACGIH : American Conference of Governmental Industrial Hygienists, Inc.

WEEL : Workplace Environmental Exposure Level

HAZ DES : Hazard Designation

Action Level A value set by OSHA that is lower than the PEL which will trigger the

need for activities such as exposure monitoring and medical surveillance

if exceeded.

Americas Styrenics LLC urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific SDSs, we are not and cannot be responsible for SDSs obtained from any source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.

09/27/2021 11/11